

Amendments to the Claims

The following listing of the claims replaces all previous listings of the claims:

1. (Currently Amended) An anchoring for a strip-shaped traction element ~~elements~~ on a supporting structure that is under tension, comprising a base plate attached to the supporting structure and a clamping plate clamped against the base plate and fixed by adhesion and clamping, wherein the clamping plate is supported on the base plate in a positive fit in a direction ~~of a traction force of~~ tension in the traction element, wherein the clamping plate comprises a substantially integral downwardly protruding securing tappet which engages a securing surface of the base plate.
2. (Currently Amended) An anchoring according to Claim 1, wherein the clamping plate, on either side of the traction element, comprises, in each case, a downwardly protruding securing tappet which engages, in each case, a securing ~~recess~~ surface of the base plate.
3. (Currently Amended) ~~An anchoring according to Claim 1~~ An anchoring for a strip-shaped traction element on a supporting structure that is under tension, comprising a base plate attached to the supporting structure and a clamping plate clamped against the base plate and fixed by adhesion and clamping, wherein the clamping plate is supported on the base plate in a positive fit in a direction of tension in the traction element, wherein the clamping plate exhibits, on either side, in each case, a securing protrusion which is supported, in each case, against a substantially integral, upwardly extending stop that is connected with the base plate.

4. (Currently Amended) ~~An anchoring according to Claim 1~~ An anchoring for a strip-shaped traction element on a supporting structure that is under tension, comprising a base plate attached to the supporting structure and a clamping plate clamped against the base plate and fixed by adhesion and clamping, wherein the clamping plate is supported on the base plate in a positive fit in a direction of tension in the traction element, wherein the clamping plate, with its front surface facing in the direction of tension in the traction element ~~the traction force~~, is supported against two substantially integral, upwardly extending stops that are connected with the base plate.

5. (Previously Presented) An anchoring according to Claim 4, wherein the stops on the base plate are welded-on push blocks.

6. (Currently Amended) An anchoring according to claim 1, wherein the clamping plate is fixed in position by a positioning device which engages the clamping plate in the direction of tension in the traction element ~~the traction force~~ in positive fitting support against the base plate.

7. (Previously Presented) An anchoring according to Claim 6, wherein the positioning device is adapted to be removed from the anchoring.

8. (Previously Presented) An anchoring according to Claim 6, wherein the positioning device comprises a threaded rod disposed between the clamping plate and a bridge that is connected with the base plate.

9. Canceled.

10. (Previously Presented) An anchoring according to Claim 6, wherein the positioning device comprises a removable threaded collet.

11. (Previously Presented) An anchoring according to Claim 3, wherein the stops on the base plate are welded-on push blocks.

12. (Currently Amended) An anchoring according to claim 2, wherein the clamping plate is fixed in position by a positioning device which engages the clamping plate in the direction of tension in the traction element ~~the traction force~~ in positive fitting support against the base plate.

13. (Currently Amended) An anchoring according to claim 3, wherein the clamping plate is fixed in position by a positioning device which engages the clamping plate in the direction of tension in the traction element ~~the traction force~~ in positive fitting support against the base plate.

14. (Currently Amended) An anchoring according to claim 4, wherein the clamping plate is fixed in position by a positioning device which engages the clamping plate in the direction of tension in the traction element ~~the traction force~~ in positive fitting support against the base plate.

15. (Currently Amended) An anchoring according to claim 5, wherein the clamping plate is fixed in position by a positioning device which engages the clamping plate in the direction of tension in the traction element ~~the traction force~~ in positive fitting support against the base plate.

16. (Currently Amended) An anchoring according to claim 11, wherein the clamping plate is fixed in position by a positioning device which engages the clamping plate in the direction of tension in the traction element ~~the traction force~~ in positive fitting support against the base plate.

17. (Currently Amended) An anchoring according to claim 8, wherein the threaded rod extends in the direction of tension in the traction element ~~the traction force~~.

18. (Previously Presented) An anchoring according to claim 1, wherein the traction element is fixed between the base plate and the clamping plate by adhesive on sides of the traction element facing the base plate and the clamping plate and by clamping.

19. (Currently Amended) An anchoring according to claim 1, wherein tension in the traction element ~~the traction force~~ is transferred substantially equally from the traction element to the base plate and the clamping plate.